

## List of Figures

- |   |   |
|---|---|
| <b>Fig.2.1:</b> Geometry of the problem   | <b>Fig.2.12:</b> Shear stresses for different $N$ when $M^2 = 5$ and $Gr = 50$  |
| <b>Fig.2.2:</b> Variation of velocity for different $N$ when $M^2 = 5$ , $r_T = 0.4$ and $Gr = 100$               | <b>Fig.2.13:</b> Shear stresses for different $M^2$ when $N = 4$ and $Gr = 50$  |
| <b>Fig.2.3:</b> Variation of velocity for different $M^2$ when $N = 4$ , $r_T = 0.4$ and $Gr = 100$               | <b>Fig.3.1:</b> Geometry of the problem   |
| <b>Fig.2.4:</b> Variation of velocity for different $Gr$ when $M^2 = 5$ , $N = 4$ and $r_T = 0.4$                 | <b>Fig.3.2:</b> Steady primary velocity $u_0$ and steady secondary velocity $v_0$ corresponding to the steady uniform velocity $U_0$ for $K^2$ with $M^2 = 5$ |
| <b>Fig.2.5:</b> Variation of velocity for different $r_T$ when $M^2 = 5$ , $N = 4$ and $Gr = 100$                 | <b>Fig.3.3:</b> Steady primary velocity $u_0$ and steady secondary velocity $v_0$ corresponding to the steady uniform velocity $U_0$ for $M^2$ with $K^2 = 4$ |
| <b>Fig.2.6:</b> Variation of induced magnetic field for different $N$ when $M^2 = 5$ , $r_T = 0.4$ and $Gr = 100$ | <b>Fig.3.4:</b> Unsteady primary velocity $u_{\text{uns}}$ for $K^2$ with $M^2 = 5$ , $\omega = 12$ and $\omega\tau = 90^\circ$                               |
| <b>Fig.2.7:</b> Variation of induced magnetic field for different $M^2$ when $N = 4$ , $r_T = 0.4$ and $Gr = 100$ | <b>Fig.3.5:</b> Unsteady secondary velocity $v_{\text{uns}}$ for $K^2$ with $M^2 = 5$ , $\omega = 12$ and $\omega\tau = 90^\circ$                             |
| <b>Fig.2.8:</b> Variation of induced magnetic field for different $Gr$ when $N = 4$ , $r_T = 0.4$ and $M^2 = 5$   | <b>Fig.3.6:</b> Unsteady primary velocity $u_{\text{uns}}$ for $\omega$ with $M^2 = 5$ , $K^2 = 4$ and $\omega\tau = 90^\circ$                                |
| <b>Fig.2.9:</b> Variation of induced magnetic field for different $r_T$ when $N = 4$ , $M^2 = 5$ and $Gr = 100$   | <b>Fig.3.7:</b> Unsteady secondary velocity $v_{\text{uns}}$ for $\omega$ with $M^2 = 5$ , $K^2 = 4$ and $\omega\tau = 90^\circ$                              |
| <b>Fig.2.10:</b> Variation of temperature for different $N$ when $r_T = 0.4$                                      | <b>Fig.3.8:</b> Unsteady velocity distributions $u_{\text{uns}}$ and $v_{\text{uns}}$ for $\omega\tau$ with $M^2 = 5$ , $\omega = 12$ and $K^2 = 4$           |
| <b>Fig.2.11:</b> Variation of temperature for different $r_T$ when $N = 4$  | <b>Fig.4.1:</b> Physical configuration  |

- Fig.4.2(a):** Primary velocity profiles  $u_1$  varying  $M^2$
- Fig.4.2(b):** Secondary velocity profiles  $w_1$  varying  $M^2$
- Fig.4.2(c):** Primary velocity profiles  $u_1$  varying  $K^2$
- Fig.4.2(d):** Secondary velocity profiles  $w_1$  varying  $K^2$
- Fig.4.2(e):** Primary velocity profiles  $u_1$  varying  $Re$
- Fig.4.2(f):** Secondary velocity profiles  $w_1$  varying  $Re$
- Fig.4.2(g):** Primary velocity profiles  $u_1$  varying  $n\tau$
- Fig.4.2(h):** Secondary velocity profiles  $w_1$  varying  $n\tau$
- Fig.4.3(a):** Temperature profiles varying  $Re$
- Fig.4.3(b):** Temperature profiles varying  $Pr$
- Fig.4.3(c):** Temperature profiles varying  $Ec$
- Fig.4.3(d):** Temperature profiles varying  $\delta$
- Fig.4.3(e):** Temperature profiles varying  $Bi_1$
- Fig.4.3(f):** Temperature profiles varying  $Bi_2$
- Fig.4.3(g):** Temperature profiles varying  $\tau$
- Fig.4.3(h):** Time evolution of temperature profiles varying  $\eta$  and  $\tau$
- Fig.4.4(a):** Shear stress  $\tau_{x_0}$  varying  $K^2$
- Fig.4.4(b):** Shear stress  $\tau_{z_0}$  varying  $K^2$
- Fig.4.4(c):** Shear stress  $\tau_{x_0}$  varying  $Re$
- Fig.4.4(d):** Shear stress  $\tau_{z_0}$  varying  $Re$
- Fig.4.4(e):** Shear stress  $\tau_{x_0}$  varying  $n\tau$
- Fig.4.4(f):** Shear stress  $\tau_{z_0}$  varying  $n\tau$
- Fig.5.1:** Sketch of physical problem and coordinate system
- Fig.5.2(a):** Velocity profiles varying  $M^2$
- Fig.5.2(b):** Velocity profiles varying  $C$
- Fig.5.2(c):** Velocity profiles varying  $Da$
- Fig.5.2(d):** Velocity profiles varying  $\lambda$
- Fig.5.3(a):** Temperature distributions varying  $M^2$
- Fig.5.3(b):** Temperature distributions varying  $Da$
- Fig.5.3(c):** Temperature distributions varying  $\lambda$
- Fig.5.3(d):** Temperature distributions varying  $N$
- Fig.5.3(e):** Temperature distributions varying  $Pr$
- Fig.5.3(f):** Temperature distributions varying  $Ec$

- Fig.5.4(a):** Variation of stream lines when  $M^2 = 0$ ,  $C = 1$ ,  $Da = 0.1$ ,  $\lambda = 0.5$
- Fig.5.4(b):** Variation of stream lines when  $M^2 = 10$ ,  $C = 1$ ,  $Da = 0.1$ ,  $\lambda = 0.5$
- Fig.5.4(c):** Variation of stream lines when  $Da = 0.01$ ,  $C = 1$ ,  $M^2 = 5$ ,  $\lambda = 0.5$
- Fig.5.4(d):** Variation of stream lines when  $Da = 0.1$ ,  $C = 1$ ,  $M^2 = 5$ ,  $\lambda = 0.5$
- Fig.5.4(e):** Variation of stream lines when  $C = 0$ ,  $M^2 = 5$ ,  $Da = 0.1$ ,  $\lambda = 0.5$
- Fig.5.4(f):** Variation of stream lines when  $C = 5$ ,  $M^2 = 5$ ,  $Da = 0.1$ ,  $\lambda = 0.5$
- Fig.5.4(g):** Variation of stream lines when  $\lambda = 0$ ,  $M^2 = 5$ ,  $C = 1$ ,  $Da = 0.1$
- Fig.5.4(h):** Variation of stream lines when  $\lambda = 1$ ,  $M^2 = 5$ ,  $C = 1$ ,  $Da = 0.1$
- Fig.6.1 :** Physical configuration
- Fig.6.2(a):** Primary velocity profiles  $u_1$  varying  $M^2$  when  $N = 2$ ,  $m = 0.5$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(b):** Secondary velocity profiles  $w_1$  varying  $M^2$  when  $N = 2$ ,  $m = 0.5$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(c):** Primary velocity profiles  $u_1$  varying  $m$  when  $N = 2$ ,  $M^2 = 10$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(d):** Secondary velocity profiles  $w_1$  varying  $m$  when  $N = 2$ ,  $M^2 = 10$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(e):** Primary velocity profiles  $u_1$  varying  $N$  when  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(f):** Secondary velocity profiles  $w_1$  varying  $N$  when  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(g):** Primary velocity profiles  $u_1$  varying  $Gr$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(h):** Secondary velocity profiles  $w_1$  varying  $Gr$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.2(i):** Primary velocity profiles  $u_1$  varying  $Pr$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$  and  $\tau = 0.5$
- Fig.6.2(j):** Secondary velocity profiles  $w_1$  varying  $Pr$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$  and  $\tau = 0.5$
- Fig.6.2(k):** Primary velocity profiles  $u_1$  varying  $\tau$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$  and  $Pr = 0.71$
- Fig.6.2(l):** Secondary velocity profiles  $w_1$  varying  $\tau$  when  $N = 2$ ,  $m = 0.5$ ,  $M^2 = 10$ ,  $Gr = 5$  and  $Pr = 0.71$

- Fig.6.3(a):** Time evolution of  $u_1$ -profiles varying  $\eta$  and  $\tau$  for impulsive motion
- Fig.6.3(b):** Time evolution of  $u_1$ -profiles varying  $\eta$  and  $\tau$  for accelerated motion
- Fig.6.3(c):** Time evolution of  $w_1$ -profiles varying  $\eta$  and  $\tau$  for impulsive motion
- Fig.6.3(d):** Time evolution of  $w_1$ -profiles varying  $\eta$  and  $\tau$  for accelerated motion
- Fig.6.4(a):** Temperature profiles varying  $N$  when  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.4(b):** Temperature profiles varying  $Pr$  when  $N = 2$  and  $\tau = 0.5$
- Fig.6.4(c):** Temperature profiles varying  $\tau$  when  $N = 2$  and  $Pr = 0.71$
- Fig.6.4(d):** Time evolution of temperature profiles varying  $\eta$  and  $\tau$  when  $N = 2$  and  $Pr = 0.71$
- Fig.6.5(a):** Shear stress  $\tau_x$  varying  $M^2$  when  $N = 2$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.5(b):** Shear stress  $\tau_z$  varying  $M^2$  when  $N = 2$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $\tau = 0.5$
- Fig.6.5(c):** Shear stress  $\tau_x$  varying  $N$  when  $Gr = 5$ ,  $Pr = 0.71$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(d):** Shear stress  $\tau_z$  varying  $N$  when  $Gr = 5$ ,  $Pr = 0.71$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(e):** Shear stress  $\tau_x$  varying  $Gr$  when  $N = 2$ ,  $Pr = 0.71$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(f):** Shear stress  $\tau_z$  varying  $Gr$  when  $N = 2$ ,  $Pr = 0.71$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(g):** Shear stress  $\tau_x$  varying  $Pr$  when  $N = 2$ ,  $Gr = 5$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(h):** Shear stress  $\tau_z$  varying  $Pr$  when  $N = 2$ ,  $Gr = 5$ ,  $M^2 = 10$  and  $\tau = 0.5$
- Fig.6.5(i):** Shear stress  $\tau_x$  varying  $\tau$  when  $N = 2$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $M^2 = 10$
- Fig.6.5(j):** Shear stress  $\tau_z$  varying  $\tau$  when  $N = 2$ ,  $Gr = 5$ ,  $Pr = 0.71$  and  $M^2 = 10$
- Fig.6.6(a):** Rate of heat transfer varying  $Pr$  when  $\tau = 0.5$
- Fig.6.6(b):** Rate of heat transfer varying  $\tau$  when  $Pr = 0.71$
- Fig.7.1 :** Geometry of the problem
- Fig.7.2(a):** Primary velocity profiles across the channel with increasing time when  $M^2 = 10$ ,  $m = 0.2$  and  $Re = 0.5$
- Fig.7.2(b):** Secondary velocity profiles across the channel with increasing time when  $M^2 = 10$ ,  $m = 0.2$  and  $Re = 0.5$

- Fig.7.3(a):** Primary velocity for different  $M^2$  when  $Re = 0.5$ ,  $m = 0.2$  and  $\tau = 0.6$
- Fig.7.3(b):** Secondary velocity for different  $M^2$  when  $Re = 0.5$ ,  $m = 0.2$  and  $\tau = 0.6$
- Fig.7.4(a):** Primary velocity for different  $m$  when  $Re = 0.5$ ,  $M^2 = 10$  and  $\tau = 0.6$
- Fig.7.4(b):** Secondary velocity for different  $m$  when  $Re = 0.5$ ,  $M^2 = 10$  and  $\tau = 0.6$
- Fig.7.5(a):** Primary velocity for different  $Re$  when  $M^2 = 10$ ,  $m = 0.2$  and  $\tau = 0.6$
- Fig.7.5(b):** Secondary velocity for different  $Re$  when  $M^2 = 10$ ,  $m = 0.2$  and  $\tau = 0.6$
- Fig.7.6(a):** Primary velocity for different  $\tau$  when  $Re = 0.5$ ,  $m = 0.2$  and  $M^2 = 10$
- Fig.7.6(b):** Secondary velocity for different  $\tau$  when  $Re = 0.5$ ,  $m = 0.2$  and  $M^2 = 10$
- Fig.7.7(a):** Shear stress  $\tau_{x_1}$  for different  $M^2$  when  $Re = 2$  and  $\tau = 0.5$
- Fig.7.7(b):** Shear stress  $\tau_{z_1}$  for different  $M^2$  when  $Re = 2$  and  $\tau = 0.5$
- Fig.7.8(a):** Shear stress  $\tau_{x_1}$  for different  $Re$  when  $M^2 = 10$  and  $\tau = 0.5$
- Fig.7.8(b):** Shear stress  $\tau_{z_1}$  for different  $Re$  when  $M^2 = 10$  and  $\tau = 0.5$
- Fig.7.9:** Temperature profiles across the channel with increasing time when  $M^2 = 5$ ,  $m = 0.1$ ,  $Re = 1$ ,  $Pr = 0.72$ ,  $Ec = 0.1$ ,  $\delta = 0.1$ ,  $\lambda = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.10:** Temperature profiles for different  $M^2$  when  $Re = 1$ ,  $Pr = 0.72$ ,  $m = 0.1$ ,  $Ec = 0.1$ ,  $\lambda = 0.1$ ,  $\delta = 0.1$ ,  $\tau = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.11:** Temperature profiles for different  $m$  when  $M^2 = 5$ ,  $Pr = 0.72$ ,  $Re = 1$ ,  $Ec = 0.1$ ,  $\delta = 0.1$ ,  $\lambda = 0.1$ ,  $\tau = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.12:** Temperature profiles for different  $Re$  when  $M^2 = 5$ ,  $Pr = 0.72$ ,  $m = 0.1$ ,  $Ec = 0.1$ ,  $\lambda = 0.1$ ,  $\delta = 0.1$ ,  $\tau = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.13:** Temperature profiles for different  $\delta$  when  $M^2 = 5$ ,  $Pr = 0.72$ ,  $m = 0.1$ ,  $Ec = 0.1$ ,  $Re = 1$ ,  $\lambda = 0.1$ ,  $\tau = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.14:** Rate of heat transfer  $\theta'(1, \tau)$  for different  $Re$  when  $Ec = 0.1$ ,  $m = 0.1$ ,  $Pr = 0.72$ ,  $M^2 = 5$ ,  $\delta = 0.1$ ,  $\lambda = 0.1$  and  $\varepsilon = 0.1$
- Fig.7.15:** Rate of heat transfer  $\theta'(1, \tau)$  for different  $\delta$  when  $Re = 1$ ,  $m = 0.1$ ,  $Pr = 0.72$ ,  $M^2 = 5$ ,  $Ec = 0.1$ ,  $\lambda = 0.1$  and  $\varepsilon = 0.1$