

List of Tables

2.1	Range table used in graph neighbourhood based scheme	37
2.2	Pixel matrix used in graph neighbourhood based scheme	37
2.3	Group numbering of pixels according to their range in range table	38
2.4	Degree of neighbourhood of pixels in a pixel block	38
2.5	Selected pixels in a pixel block for a particular threshold value	38
2.6	Y component of YCbCr components of an image	39
2.7	DCT coefficient matrix of a (8×8) image block	39
2.8	Sample quantization table for Y component	39
2.9	Sample quantization table for Cb and Cr components	39
2.10	Quantized DCT coefficient matrix of Y component	40
3.1	Results of evaluation metrics using standard images for varying threshold values from 1 to 8 in SSGN	54
3.2	Comparison of SSGN with some state-of-the-art schemes in terms of PSNR (dB) when payload is 10000 bits	55
3.3	Comparison of SSGN with some state-of-the-art schemes in terms of PSNR (dB) when payload is 20000 bits	56
3.4	Results of RS analysis in SSGN	57
3.5	Comparison table of proposed scheme with existing schemes in terms of PSNR (dB) and Capacity in SSPVD	64
3.6	Table for PSNR, SSIM, and NCC of different images in SSPVD	65
3.7	Results of RS analysis in SSPVD	66
3.8	Standard deviation (SD) and correlation coefficient (CC) of cover image and stego image in SSPVD	67
3.9	Relative entropy between original image and stego image in SSPVD	68

3.10	Comparison of SSGN and SSPVD in terms of PSNR (dB) and payload (bpp)	69
3.11	Comparison of steganalysis values of SSGN and SSPVD	69
4.1	Experimental results after embedding maximum amount of secret information in DSGN	81
4.2	Comparison of proposed scheme with existing dual image based schemes in terms of PSNR(dB) and payload(bpp) in DSGN	82
4.3	Comparison of proposed scheme with existing reversible data hiding schemes in terms of average PSNR (dB) and payload (bpp) in DSGN	82
4.4	Results of RS analysis in DSGN	82
4.5	Experimental results after embedding maximum amount of secret information in DSWM	97
4.6	Comparison of proposed scheme with existing dual image based scheme in terms of PSNR(dB) and payload(bpp) in DSWM	98
4.7	Comparison of proposed scheme with existing reversible data hiding schemes in terms of average PSNR (dB) and payload (bpp) in DSWM	98
4.8	Comparison of PSNR (dB) and capacity (bits) for different image sizes in DSWM	99
4.9	Results of RS analysis in DSWM	105
4.10	Comparison between DSGN and DSWM in terms of PSNR (dB) and payload (bpp)	107
4.11	Comparison of steganalysis values of DSGN and DSWM	107
5.1	Available coefficient for data embedding, Number of bits embedded, PSNR (dB), SSIM and Q-Index of images at different QF level in SSDCT	121
5.2	Comparison of proposed scheme with some state-of-the-art schemes in terms of PSNR (dB) in SSDCT	122
5.3	Comparison of different evaluation metrics with different benchmark image datasets in SSDCT	123
5.4	Results of RS analysis in SSDCT	123
5.5	Comparison of proposed scheme with some existing schemes in terms of PSNR (dB) and SSIM in SSDWT	133

5.6	Comparison of proposed scheme with some state-of-the-art DCT based schemes in terms of PSNR(dB) in SSDWT	134
5.7	Results of different evaluation matrices for different images in SSDWT	135
5.8	Results of RS analysis in SSDWT	135
5.9	Comparison of SSDCT and SSDWT in terms of PSNR (dB) and payload (bpp)	137
5.10	Comparison of steganalysis values of SSDCT and SSDWT	137
6.1	Application areas of the proposed schemes	147